



10W-40 MOTOR OIL

THE ULTIMATE IN ENGINE PROTECTION & PERFORMANCE

Originally designed for motor racing and heavy duty industrial equipment, **ProOne® XPL+® Technology** has proven its superiority in providing the best lubrication protection, helping your vehicle maximize its performance.

- Reduces wear across a wide range of driving speeds
- Protects the engine for the entire drain interval even under extreme pressure
- Decreases engine deposit formation to help maximize engine response

ADVANTAGES:

- Extreme pressure protection
- Start-up protection
- Maximum engine protection
- Extreme temperature range +500°F
- Reduces sludge build-up
- Gasket & seal conditioner
- Oxidation resistant
- Reduces breakdowns
- Reduces downtime

MEETS API SERVICE CATEGORIES SP/SG/SN PLUS/SN/SM



American
Petroleum
Institute



WITH



SHAKE WELL BEFORE USE

TEST DESCRIPTION	UNITS	TEST METHOD	RESULTS
Appearance	-	Visual	Slight Hazy
Base Number	mg KOH/g	ASTM D-2896	14.2
Ca Content	%wt	ASTM D-4951	0.479
CCS @ -15°C	cP	ASTM D-5293	6357
Density @ 29.5°C	g/cm3	ASTM D-4052	0.8675
Flash Point	°C	ASTM D-92	206
Foam Tend/ Stab. Seq I, II, & III	ml/ml	ASTM D-892	0/0, 25/0, 0/0
Kinematic Viscosity @ 40°C	mm2/sec	ASTM D-445	93.28
Kinematic Viscosity @ 100°C	mm2/sec	ASTM D-445	14.19
Pour Point	°C	ASTM D-97	-39
Viscosity Index	-	ASTM D-2270	157
Zn Content	%wt	ASTM D-4951	0.080