



# SYNTHETIC GL-5 LIMITED SLIP GEAR OIL

## SUPERIOR 75W-90/80W-90/85W140 WITH XPL+ TECHNOLOGY

The API GL-5 Limited Slip Gear Oil is a high performance extreme pressure automotive gear lubricant for use in passenger car and truck axles with hypoid gear sets.

It is designed to meet the most stringent requirements of severe gear oil tests. It reduces oxidative sludge and varnish, dramatically reduces wear, prevents scoring, and protects against metal fatigue.



DOES NOT CONTAIN SOLIDS OR HARMFUL SOLVENTS LIKE CHLORINE

### 🔥 BOTTOM LINE BENEFITS:

- High film strength
- Designed for severe applications with high loads
- High RPM use
- Dramatically reduces friction, heat & wear
- Thermal stability over wide temperature range
- Provides oxidation stability
- Rust & corrosion inhibitor
- Compatible with seals and gaskets
- Eliminates gear housing chatter
- Good foam resistance

### 🔥 PHYSICAL PROPERTIES:

Characteristic (SAE Grade)	75W-90	80W-90	85W-140
cSt @ 40°C (104°F)	101	138	334
cSt @ 100°C (212°F)	15.0	14.5	25
Viscosity Index (ASTM D-2270)	155	104	97
Flash Point, °C (ASTM D-92)	>194	>220	>220
Specific Gravity (ASTM D-1298)	0.88	0.88	0.89
Pour Point °C (ASTM D-2270)	-45	-32	-12

### 🔥 BASE OIL MEETS FOLLOWING SPECIFICATIONS

**API Service** GL-5, MT-1

**Ford**  
WSP-M2C197-A (SAE 80W-90)  
MIL-PRF-2105E

**ArvinMeritor**  
O76-A (SAE 85W-140)  
O76-D (SAE 80W-90)  
O76-D (SAE 75W-90)

**Mack GO-J** SAE J2360

ProOne#	Description	Size
25005-75	75W-90 GL5	5 gallon/ 18.9L Pail
25055-75	75W-90 GL5	55 gallon/ 208L Drum

ProOne#	Description	Size
25005-80	80W-90 GL5	5 gallon/ 18.9L Pail
25055-80	80W-90 GL5	55 gallon/ 208L Drum

ProOne#	Description	Size
25005-85	85W-140	5 gallon/ 18.9L Pail
25055-85	85W-140	55 gallon/ 208L Drum

Use at 100%. Follow manufacturers recommendation